# FIRST OF THE NEW BREED imageCLASS LBP253x

Entry Level WORKHORSE RANGE – ADVANCE Mono Laser Printer

## Fast and efficient, the LBP253x will impress you with its new look and feel. Whether it is used as a standalone printer, or built into an MDS solution with the uniFLOW software embedded — this is the perfect entry level printer for your business.

The imageCLASS LBP253x is the latest model in Canon's new "LBP ADVANCE" range. LBP ADVANCE models designed with the customer in mind and to complement business' existing printing environments. With features such as a 3.5 inch colour touch screen, integrated PCL & Genuine Adobe PostScript, MEAP compatibility to allow the embedding of MEAP applications & compatibility with FM Audit & Print Fleet, this is the perfect complement to your business.

### **Key Features**

#### **MEAP-Embedded**

 With the embedded MEAP environment, users are able to utilise uniFLOW, to enhance their workflows and increase productivity.

## Genuine Adobe PostScript, & PCL Compatible

• The LBP253x features genuine Adobe PostScript to ensure the best results when used in a PS environment. Further it also supports both PCL, making it ideal for use in both small to large organisations with established print solutions.

# Low Power Consumption and Quick Start Up

 By adopting Canon's unique On-Demand Fixing System, the LBP253x achieves low power consumption of less than 13.2 watts (average) in standby and quick start-up, with first page out in less than 6 seconds.

#### Enhanced Security

• Organisations can now eliminate unnecessary printing, while ensuring the security of sensitive documents with the LBP253x's Secure Print features.

This can be configured using the printers memory for a server-less solution, or run

via uniFLOW, which can be embedded onto the machine via MEAP.

Ease of Use and Paper Capacity

Organisations can add an optional
500 sheet cassette giving a total of
800 sheet from 3 sources, ensuring
continual printing, or a selection of 3
different media types. The LBP253x's
3.5 inch colour touch screen takes the
user to a new level in Ease of Use and
Operation, making it a pleasure to use.

#### eRDS capability

 Direct access to e-Maintenance via eRDS, so there is no need for an EMAGENT

## On Demand Fixing

Canon's unique On Demand Fixing system offers low power consumption and fast recovery times from standby mode

## 

Integrated network connection to easily share amongst many users within the office

## Automatic Image Refinement

Increases the resolution of the print up to an equivalent of 1200 x 1200 dpi ensuring that you get a professional looking document every time



## Auto Duplex

Auto duplex for easy double sided printing and cost savings

Subject to change without notice.

# Canon

## Fast Print Speed

Offering up to 33 ppm print speeds with a 6 sec 1st print out so you will never be waiting for a print again



#### PCL, Genuine Adobe PostScript Support

Supports common printer languages for seamless integration into an existing print solution

## mean Powered By MEAP

Running MEAP applications such as uniFLOW is no problem with the LBP253x's integrated MEAP environment

# Compatibility with FM Audit / Print Fleet

Compatibility with FM Audit & Print Fleet for easy inclusion into multi-vendor MPS solutions



# Low Power Consumption in Standby

By offering reduced power consumption, Canon Laser Printers will save you money help the environment

### Laser Printers

Canon laser printers combine a range of features and technologies to deliver fast, high quality and reliable printing. So, if you are looking to create professional business documents while reducing your running costs, Canon lasers fit the bill.



## imageCLASS LBP253x Workhorse range – ADVANCE Mono Laser Printer

#### Print Method

Machine Type	Black & White laser beam printer
Fixing Method	On Demand Fixing
FPOT	6 sec
Print Speed <sup>1</sup>	
Mono: A4/letter (1-sided printing )	33/35ppm
Duplex: A4/letter (2-sided printing)	16.8/17 pages/min. 8.4/8.5 sheets/min
Resolution	600 dpi × 600 dpi, 1200 dpi x 1200 dpi equivalent, 2400 dpi equivalent × 600 dpi
Media Handling	
Paper Input (based on 64g/m²)	Standard: 250 sheet cassette Multi-purpose tray: 50 sheets Option: 500 sheets Maximum paper capacity: (PF-44 optional paper cassette) 800 sheets
Paper output (based on 64g/m²)	Face-down: 150 sheets Face-up: 1 sheet
Paper size	Standard: A4/B5/A5/A6/LGLULTR/EXECTIVE/16K/ Custom sizes (Width:105.0 to 215.9mm, Length: 148.0 to 355.6mm) Option: A4/B5/A5/A6/LGULTR/EXECTIVE/16K/ Custom sizes (Width:105.0 to 215.9mm, Length: 148.0 to 355.6mm) Multi-purpose tray: A4/B5/A5/A6/LGL/LTR/ EXECTIVE/16K/Envelop COM- 0/Monarch/DL/C5/ B5(ISO)/Index Card/Custom sizes (Width: 76.2 to 215.9mm, Length: 127.0 to 355.6mm)
Paper weight	Standard: 60–120g/m² Option: 60–120g/m² Multi-purpose tray: 60–163g/m²
Paper type	Plain paper, Heavy Paper, Transparency, Label, Index card, Envelope, Post card
Effective Printing Area	5 mm-top, bottom, left and right (Envelope: 10 mm)
Duplex Printing	Standard (only A4/LTR/LGL) (Paper Weight: 60–120g/m²)

General Features	
Warm-up time (when the printer is turned on)	16 sec or less
Recovery time (from sleep mode)	9 sec or less
Memory (RAM)	Standard: 1GB Maximum: 1GB
Operation mode	Page description language: PCL5e/6, UFR-II, PostScript level3
Standard font	PCL Font: 93 / PS Font: 136 (std)
Operation Panel	3.5 inch QVGA colour touch screen
I/F	USB: Hi-Speed USB (1) USB (1 on the back) Network:10Base-T/100Base-TX,1000Base-T Wi-Fi 802.11b/g/n, Apple AirPrint, Google Cloud Print, Mopria
Compatible operating systems	Win10(32/64bit)/Win8.1 (32/64bit)/8(32/64bit)/7 (32/64bit)/Vista(32/64bit) Server 2012 R2(64bit)/Server 2012(64bit)/Server 2008 R2(64bit)/Server 2008 (32/64bit)/Server 2003R2 (32/64bit)/Server 2003 (32/64bit)/ Mac OS 10.5.8/Linux
Noise level	During operation: 54.2dB or less (by sound pressure level) During standby: Inaudible (by sound pressure level)
Power consumption (W)	Operation: Approx. 560 W During standby: Approx. 14 W During sleep: Approx. 14W/14W (Panel off) Approx. 1W/1W (Deep sleep)
Dimensions (W × D × H)	403mm x 377mm x 317mm
Weight (kg) without CRG	Approx. 11.6kg (approx.23.4lb)
Power requirement	AC 220-240V (±10%) 50/60Hz (±2Hz)
Operating environment	Temperature: 10–30°C Humidity: 20–80%RH (no condensation)
Duty Cycle	50,000 pages
Toner Specifications	
Cartridges <sup>2</sup>	CART319: yields 2,100 pages CART319II: yields 6,400 pages



LAS-2YOS-1 – 3 year Extended Onsite Service & Support card

1. Print speed may vary with the content of the document and the processing speed of the host computer. Time from when print data is received.

speed of the host computer. Time from when prin
 Incompliance with ISO/IEC 19798.

Subject to change without notice.

canon.com.au/business Follow us on Twitter @CanonBusinessAU 1800 444 199 4243-v1-02/16



achieve more.