TOSHIBA

B-EX6 INDUSTRIAL PRINTER

Product brochure

- The Toshiba B-EX6 series is redefining the industrial printer marketplace. Combining market leading technology with usability, reliability and a low total cost of ownership.
- Extending the capabilities of our existing range of B-EX printers to cover the most demanding applications, for heavy duty industrial printing.
- > Rugged and durable design, advanced functionality, cost saving features and a wide choice of models and options for the best "all-in-one" industrial solution.





FLEXIBLE. DURABLE. RELIABLE.

Cost of Ownership

Featuring our unique Near Edge Technology, the B-EX6 is capable of running at high speeds with the added benefit of a 30% increase in ribbon capacity (800m)² to reduce your down time. Toshiba Genuine B-EX6 ribbons feature silicone protection*, ensuring maximum ROI with extended print head longevity.

Flexible Design

The B-EX6 has been designed with the same durability and reliability as the B-EX4 range, with rugged and robust outer casing. The B-EX4 now features a bi-cover to reduce footprint and opening space for ease of operation, reduced maintenance costs and minimal down-time.

Improve your efficiency

Supporting 6 inch media, with speeds of up to 12 inches per second, the B-EX6 range can handle the most demanding printing applications. In addition, high output is facilitated with advanced processing capabilities, increasing overall efficiency and productivity.

Enhanced connectivity

For flexible connectivity options, USB and Ethernet come as standard on the B-EX6 series. The optional Bluetooth functionality allows for parameter settings directly from your smart phone or mobile device.

Range of Models

A choice of models to suit any application, with 200 and 300 dpi variants for superior print quality and perfect readability of barcodes. Flat head and near edge head models enable easy replacement of legacy printer estates, a wide range of media and options offer flexibility for any printing application.

Applications

The B-EX6 series combines the tried and trusted features and functionality of the current B-EX range.

Reliability and performance usually come at a cost however, with the B-EX series, premium capabilities come as standard, essentially lowering initial capital outlay and future-proofing your investment.

- > Industrial & Manufacturing
 - Automotive, Chemical, Pharmaceutical, Textile, Electronics, Food & Beverages
- > Government
 - Utilities
- > Retail Distribution
- > Transport and Logistics
- > Healthcare
- > Telecommunications

Key Highlights

- Combining market leading technology with usability, reliability and a low total cost of ownership
- > High speed; high output
- > Rugged, robust and durable, with easy operation



Improved productivity, lower cost of ownership.

^{*} Refer to Toshiba Genuine datasheets

SPECIFICATIONS

General

Print Method Direct thermal/Thermal transfer

Printhead T1: Near edge technology

T3: Flat head

Dimensions (W x D x H) 331 x 460 x 310 mm

Weight 20 kg

User interface Graphic LCD, 2 x LED, 10 x key

Operating Temperature / 5°C to 40°C / 25-85% non-condensing

Humidity relative humidity (RH)

Power supply 240V, 50 Hz

Print

Resolution 203/305 dpi (8/12 dots/mm)

Maximum Print Speed 76/127/203/254/305 mm/second (3/5/8/10/12 ips)

Maximum Print Width 160 mm

Maximum Print Length 1,490 mm

Barcodes UPC/EAN/JAN, Code 39, Code 93, Code 128,

EAN 128, NW7, MSI, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Postnet, RM4SCC, KIX-Code,

Customer Barcode, GS1 Databar

2D Codes Data Matrix, PDF 417, Maxicode, QR Code,

Micro PDF 417, CP Code

Fonts Bitmap font, Outline font, Price font, TTF, OFT

Media

Alignment Centre

Backing Paper Width 50-165 mm

Label Thickness 0.13-0.17 mm

Tag Thickness 0.08-0.25mm

Inner Media Core Diameter 40-76.2 mm

Outer media Roll Diameter 200 mm

Media Type Roll, Fanfold

Software & Connectivity

Emulation ZPL II

Printer Driver Windows 10/8/7/Vista (32/64 bit),

Windows Server 2012/Server 2008 (32/64 bit)

USB 2.0, LAN 10/100 Base, IPv6, USB Host/RTC, RS232¹⁾, Centronics¹⁾, Wireless LAN¹⁾, EX I/O¹⁾

Language Mode TPCL, BCI (function)

Label Software BarTender UltraLite

Options

Interface

Disc cutter, Peel-off module, Fan fold guide, RS232, Centronics, Wireless LAN, EX $\rm I/O, RFID^2)$





Ribbon

Ribbon Width max. 170 mm

Ribbon Core Size 25.4 mm (1 inch)

Max. Ribbon Length Standard 600 m, Optional 800 m

Max. Ribbon Diameter 90 mm

Toshiba Genuine Ribbons

Toshiba Genuine ribbons save you money.

Did you know Toshiba has a full range of approved thermal ribbons, for any printer or application?

Toshiba Genuine ribbons feature our unique Near Edge Technology, which enables fast keying time and no show through print.

For crisp barcodes, low energy settings and high speed solutions, contact us today.

Toshiba Genuine: Join the Near Edge Revolution.



¹⁾ Optional

²⁾ For T1 model only

About Toshiba

Toshiba (Australia) Pty Limited is part of the globally operating Toshiba Tec Corporation, active in various high-tech industrial sectors.

Toshiba is a leading provider of information technology, operating across multiple industries - ranging from retail, education and business services to hospitality and manufacturing. With headquarters in Japan and over 80 subsidiaries worldwide, Toshiba Tec Corporation helps organisations transform the way they create, record, share, manage and display information. For more information please contact us:

TOSHIBA (Australia) Pty Limited

Building C, 12-24 Talavera Road, North Ryde. 2113. Australia **Tel:** 1300 794 202

New Zealand

58 Lunn Avenue, Mt Wellington

Tel: 09 570 8530

www.toshiba-business.com.au www.toshiba-business.co.nz

Γ	コ	Together Information is Toshiba's vision for how people and organisations create, record, share, manage and display ideas and data.
		It is based on our belief that the most successful organisations are those that communicate information in the most efficient way .
		We make that possible through an integrated portfolio of industry-specific solutions, all of which reflect Toshiba's commitment to the future of the planet.
		For more information please visit www.toshiba-business.com.au
L		

This Class 1 laser product complies with IEC60825-1. Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation. Productivity and paper specifications are related to paper size of A4 and a paper weight of 80 g/m² if not otherwise mentioned.