

Small businesses and corporate workgroups depend on solutions that help maximise resources, boost productivity, and are easy to manage. The cost-efficient imageRUNNER 1643P can do all that, and more. With fast output and high reliability, the imageRUNNER 1643P helps you accomplish a lot in a small space.



PERFORMANCE

A compact single-function printer supporting up to legal-size paper, the imageRUNNER 1643P features a smart, comfortable design that can easily fit on a desktop or in a centralised area. With a first print-out time as fast as 5.7 seconds and output up to 43 ppm, the imageRUNNER 1643P is a quick performer. The standard 650-sheet capacity can be increased to 2,300 sheets to handle many jobs without interruption.



SECURITY

Safeguard information and help ensure security compliance with the imageRUNNER 1643P. Canon's uniFLOW® solution lets users securely retrieve documents from any networked device after authentication. These models also include technology to verify that the device boot process, firmware and applications initialise without tampering.



COST CONTROL

Designed with your bottom line in mind, the Canon imageRUNNER 1643P helps minimise costs and maximise reliability while the robust design helps ensure dependable operation. Canon's uniFLOW® software can help control costs by managing, tracking and charging back usage. And simple-to-replace, high-yield consumables help keep work moving while achieving a low cost per page.





imageRUNNER 1643P SPECIFICATIONS

Print	
Printing Method	Monochrome Laser Beam Printing
Print Speed (A4)	43 ppm
Print Resolution	600 × 600 dpi
Print Quality with Image	1,200 × 1,200 dpi (equivalent)
Refinement Technology	2,400 (equivalent) × 600 dpi
Warm-Up Time (from Power On)	30 sec or less
First Print Out Time (FPOT) A4	Approx. 5.7 sec
Recovery Time (from Sleep Mode)	3.0 sec or less
Print Language	UFR II, PCL6, PostScript 3, PDF, XPS
Auto Duplex Printing	Standard
Available Paper Size for Auto Duplex Print (Based on paper weight: 60—120 gsm)	A4, Legal, Letter, Foolscap, Indian Legal
Paper Handling	
Paper Input (Based on 80 gsm)	Standard Cassette: 550 sheets Multi-Purpose Tray: 100 sheets Optional Paper Feeder: 550 sheets (x3)
Maximum Paper Capacity	2,300 sheets
Paper Output (Based on 64g/m2)	250 sheets (face down)
Paper Size	Standard Cassette, Optional Paper Feeder: A4, B5, A5, A6, Legal, Letter, Executive, Statement, Foolscap, Indian Legal Custom sizes (Width: 105.0 to 215.9mm, Length: 148.0 to 355.6mm) Multi-Purpose Tray: A4, B5, A5, A6, Legal, Letter, Executive, Statement, Foolscap, Indian Legal, Index card (3"x5"), Envelope: COM10, Monarch, DL Custom sizes (Width: 76.2 to 215.9mm, Length: 127.0 to 355.6mm)
Paper Weight	Standard Cassette, Optional Paper Feeder: 52 to 120 gsm Multi-Purpose Tray: 52 to 199 gsm
Paper Type	Plain, Heavy, Label, Bond, Envelope
Connectivity and Software	
Standard Interface	Wired: High-Speed USB 2.0, USB Host, 10Base-T/100Base-TX/1000Base-T Ethernet
Network Security	Wired: SNMPv3, IEEE802.1x, IPSec
Mobile Printing Capability	Canon PRINT Business, Canon Print Service, Google Cloud Print™, Apple AirPrint™, Mopria® Print Service
Compatible Operating Systems	Microsoft® Windows® 10 (32, 64-bit), Windows® 8.1 (32, 64-bit), Windows® 8.3 (32, 64-bit), Windows® 7, 64-bit), Windows® 7, 64-bit), Windows® 8erver 2012 R2 (64-bit), Windows® Server 2008 R2 (64-bit), Windows® Server 2008 R2 (64-bit), Windows® Server 2008 (32, 64-bit), Windows® Server 2008 R2 (64-bit), Windows® Server 2006 (64-bit), Mac OS X 10.6.° or later, Linux

General	
Device Memory	1GB
Operational Panel	5-line LCD Display + Numeric Keys
Dimensions (W × D × H)	409 mm x 376 mm x 275 mm
Weight	Approx. 11.5 kg (without cartridge)
Power Consumption	Maximum: 1,380 W or less During Operation (Avg.): Approx. 600 W During Standby (Avg.): Approx. 10.1 W During Sleep (Avg.): Approx. 1.9 W (USB connection), Approx. 1.2 W (Wired LAN connection)
Noise level	During Operation Sound Pressure Level: 54.0 dB Sound Power Level: 6.9 B During Standby Sound Pressure Level: Inaudible Sound Power Level: Inaudible
Operating Environment	Temperature: 10-30°C Humidity: 20-80% RH (no condensation)
Power Requirement	AC 220-240 V (±10%), 50/60 Hz (±2Hz)
Consumables	Cartridge: T06 20,000 pages
Monthly Duty Cycle	150,000 pages

For information and services contact

1800 444 199 0800 222 666 Canon Australia Pty Ltd Canon New Zealand Ltd

canon.com.au/business canon.co.nz/business







