

FAST AND VERSATILE

The imageRUNNER ADVANCE DX 8700 Series is an impressive high volume printer suitable for enterprise environments requiring fast output.



Canon imageRUNNER ADVANCE DX 8700 Series

Black and White Multifunction Device

S COST CONTROL

Advanced functions for big cost-saving

- Save your business money by reducing your paper wastage utilising settings such as forced job hold at the device, and blank page removal.
- Enable print policies to monitor output while also restricting users from overuse.
- Save even further with remote support to help diagnose and solve issues fast, rather than taking up the valuable time of in-house IT staff.
- Track usage and control your costs utilising Canon's uniFLOW Online Express free software.

E PERFORMANCE

Designed for high volume printing

- Our fastest printer in the range with speeds of up to 105 ppm.
- Speed up your scanning process with a single pass document feeder with up to 270 ipm.
- Huge paper supply capacity with up to 7,700 sheets with added paper decks.
- Versatile finishing capabilities and large range of media support.

« D MOBILITY

Advanced Mobile OS Support empowers workers through freedom and flexibility

- Mobile workflows are set up to easily allow users to connect, print, scan and capture using Canon PRINT Business.
- Full support for Apple and Android Mobile Printing.
- Simple and easy mobile connectivity with in-built WiFi plus options to connect through Bluetooth and Near Field Communication (NFC).

(INTEGRATION

Systems seamlessly converge for smooth operation and easy handling

- Canon's MEAP platform works to integrate both new and existing document, capture and output management systems while being partnered with relevant support technology.
- Collaborate with key line of business applications and external systems.
- For smooth, hassle-free projects, scan and convert to Microsoft[®] Word and PowerPoint[®] files.
- Supports integration with popular cloud services like Google Drive[™] and Box*.

SECURITY

Protect sensitive information with enhanced security capabilities

- Advanced control over document access ensures documents are only seen by those that are authorised.
- Integrates with existing, third-party Security Information and Event Management (SIEM) systems to help provide real-time comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialise without alterations or tampering time and money spent on various projects.

SUSTAINABILITY

Environmentally conscious technology works to achieve green initiatives for your business

- The iR-ADV DX 8700 runs efficiently to help eliminate unnecessary power consumption and is designed to reduce emissions.
- Motion sensors, sleep recovery triggers and remote shutdown are all features that contribute to ongoing sustainability.
- Minimise paper wastage with default print settings including double-sided print and black and white.






ADVANCED SCANNING

uniFLOW Online's Filing Assist* saves you time, reduces keying errors and brings consistency to your filing so you can find what you need, when you need it, anywhere you have internet access; at home, work or on the go.

Filing Assist uses pre-configured workflows that scan batches of repetitive documents including invoices, delivery notes, picking lists and orders to popular cloud services. Not only are they scanned, they are named, converted and filed – based on rules and information from the document.











CONFIGURATION



Booklet Finisher-W1 PRO

- 5,000-sheet capacity (SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5)
- Corner and Double Stapling up to 100 sheets (A4, B5), 50 sheets (A3, A4R, B4, B5R)
- Booklet-making up to 25 sheets and non-staple saddle folded capacity up to 5 sheets
- Supports optional internal 2/3 and 2/4 hole punchers



Booklet Finisher-X1

- 3-tray, 4,250-sheet capacity (A4, B5, A5R)
- Corner and double stapling up to 100 sheets (A4/B5, 80 gsm), 50 sheets (A3/B4/A4R, 80 gsm)
- Booklet-making up to 20 sheets and non-staple saddle folded capacity up to 5 sheets
- Supports optional internal 2/3 and 2/4 hole inner punchers



Booklet Finisher-AC1

- 3-tray, 3,500-sheet capacity (A4, B5, A5R) 1,750-sheet capacity (A3, B4, A4R. B5R)
- Corner and double stapling up to 65 sheets (80 gsm)
- Booklet-making up to 20 sheets and nonstaple saddle folded capacity up to 5 sheets
- Supports Eco stapling 4 sheets (80 gsm) and Staple On-demand 65 sheets (80 gsm)
- Supports optional internal 2/3 and 2/4 hole inner punchers



Staple Finisher-W1 PRO

- 5,000-sheet capacity (SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5)
- Corner and Double Stapling up to 100 sheets (A4, B5), 50 sheets (A3, A4R, B4, B5R)
- Supports optional internal 2/3 and 2/4 hole punchers



Staple Finisher-X1

- 3-tray, 4,250-sheet capacity (A4, B5, A5R)
- Corner and double stapling up to 100 sheets (A4/B5, 80 gsm), 50 sheets (A3/
- B4/A4R, 80 gsm)
- Supports optional internal 2/3 and 2/4 hole inner punchers



Staple Finisher-AC1

- 3-tray, 3,500-sheet capacity (A4, B5, A5R) 1,750-sheet capacity (A3, B4, A4R, B5R)
- Corner and double stapling up to 65 sheets (80 gsm)
- Supports Eco stapling 4 sheets (80 gsm) and Staple On-demand 65 sheets (80 gsm)
- Supports optional internal 2/3 and 2/4 hole inner punchers




Booklet Trimmer-F1 (Connects to Booklet Finisher-W1)

- Conveyer Capacity: 30 booklets
- Trim Width: 2 to 28 mm



Paper Folding Unit-J1

Z-fold, C-fold, Half Fold, . Accordion Z-fold, Double Parallel Fold



.....


Multifunction Professional Puncher-B1

- Requires X1 or W1 Finishers .
- Punch Paper Weight up to . 256 gsm
- Punch Supports up to A3



Document Insertion Unit-N1

- Insert preprinted sheets
- Up to SRA3
- Two trays
- 400-sheet total capacity .



Paper Deck Unit-E1

Supports A4, B5

•

- Media Weight 52 to 256 gsm
 - 3,500 sheets (80 gsm)





POD Deck Lite-C1

- Supports A3, B4, A4 A4R, B5R, B5, A5R, SRA3, 13" x 19"
- Media Weight 52 to 256 gsm •
- 3,500 sheets (80 gsm) •

imageRUNNER ADVANCE DX 8700 Series SPECIFICATIONS

Machine Type	A3 Monochrome Laser Multifunctional
Core Functions	Print, Copy, Scan, Send, Store and Optional Fax
Processor	1.75 GHz Dual Core Processor
Control Panel	Standard: 10.1" TFT LCD WSVGA Colour Touch Panel Optional: 10.4" TFT LCD SVGA Colour Upright Touch Panel
Memory	Standard: 3.0 GB RAM
lard Disk Drive	Standard*: 320 GB (available disk space: 250 GB)
	Optional: 250 GB, 1TB * A different initial HDD may be used.
Mirroring Hard Disk Drive	Optional
nterface Connection	Network
	Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n)
	Optional: NFC, Bluetooth Low Energy
	Others Standard: USB 2.0 (Host) x 1, USB 3.0 (Host) x1, USB 2.0 (Device) x 1
	Optional: Serial Interface, Copy Control Interface
Paper Supply Capacity (A4, 80 gsm)	
	100-sheet Multi-purpose Tray x 1 1,500-sheet Paper Deck x 2
	550-sheet Paper Cassette x 2
Paper Output Capacity (A4, 80 gsm)	Maximum: 7,700 Sheets (with POD Deck Lite-C1 or Paper Deck Unit-E1) 250 Sheets (with Copy Tray-R2).
Paper Output Capacity (A4, 60 gsin)	Maximum: 5,000 Sheets (High-volume Stack Mode "ON" with Staple Finisher-W1 PRO
- Finishing Capabilities	or Booklet Finisher-W1 Pro) With Options: Collate, Group, Offset, Staple, Saddle Stitch, Hole Punch, Eco Staple,
inisining Capabilities	Staple On-demand, Document Insertion, Z-fold, Half-fold, C-fold, Accordion-Z fold,
	Double Parallel-fold, Trimming
Supported Media Types	Multi-purpose Tray: Thin, Plain, Recycled, Colour, Heavy, Tracing, Bond, Transparency, Labels,
	Pre-punched, Letterhead, Tab
	Paper Decks (Right/Left): Thin, Plain, Recycled, Colour, Heavy, Bond, Pre-punched, Letterhead
	Paper Cassettes (Upper/Lower):
	Thin, Plain, Recycled, Colour, Heavy, Bond, Pre-punched, Letterhead, Tab* * Tab Feeding Attachment-B1 is required.
supported Media Size	Multi-purpose Tray:
	Standard Size: SRA3, A3, A4, A4R, A5*1, A5R, A6R*2, B4, B5, B5R
	Custom Size: 100.0 x 148.0 mm to 330.2 x 487.7 mm Free Size : 100.0 x 148.0 mm to 330.2 x 487.7 mm
	*1 Supported Media Weights: More than 64 gsm
	*2 Supported Media Weights: More than 91 gsm Paper Decks (Right/Left):
	Standard Size: A4, B5 Paper Cassettes (Upper/Lower):
	Standard Size: SRA3, A3, A4, A4R, A5R, B4, B5, B5R
	Custom Size: 139.7 x 182.0 mm to 330.2 x 487.7 mm
Supported Media Weights	Multi-purpose Tray: 52 to 256 gsm Paper Decks (Right/Left): 52 to 220 gsm
	Paper Cassettes (Upper/Lower): 52 to 220 gsm
Varm-up Time	Duplex: 52 to 220 gsm Quick Startup Mode: 4 seconds or less*
vann-up nine	* Time from device power-on to when the copy icon appears and is enabled to
	operate on the touch panel display. From Deep Sleep Mode: 60 seconds or less
	From Power-on: 60 seconds or less*
	* Time from device power-on, until copy ready (not print reservation).
Dimensions (W x D x H)	Standard (including 1-pass DADF and flat touch panel): 670 x 770 x 1,185 mm With Optional Upright Touch Panel: 1,170 x 770 x 1,252 mm
nstallation Space (W x D)	Basic: 1,533 x 1,353 mm (with Multi-purpose Tray/Upper-right Cover Open + Front Cover
	Open + Copy Tray) Fully Configured: 5,068 x 1,409 mm (with POD Deck Lite-C1 + Document Insertion
	Unit-N1 + Multi Function Professional Puncher-B1 + Paper Folding Unit-J1 + Booklet
	Finisher-W1 Pro + Booklet Trimmer-F1 + Main Unit Front Cover Open)
Weight	Standard: Approx. 221 kg* ¹ With Optional Upright Touch Panel: Approx. 225 kg* ²
	*1 Including DADF, flat touch panel and the toner bottle.
Print Specifications	*2 Including DADF, Upright touch panel and the toner bottle.
Print Speed	iR-ADV DX 8705: Up to 105 ppm (A4), Up to 54 ppm (A3), Up to 76 ppm (A4R), Up to 10
	ppm (A5R)
	iR-ADV DX 8795: Up to 95 ppm (A4), Up to 50 ppm (A3), Up to 69 ppm (A4R), Up to 95 ppm (A5R)
	iR-ADV DX 8786: Up to 86 ppm (A4), Up to 44 ppm (A3), Up to 63 ppm (A4R), Up to 86
Print Resolution (dpi)	ppm (A5R) 1,200 x 1,200
Page Description Languages	Standard: UFR II
	Optional: PCL 6, Adobe®PostScript® 3 [™]
Direct Print	Supported File Types: PDF, EPS, TIFF/JPEG and XPS
Printing from Mobile and Cloud	AirPrint®, Mopria [™] , Google Cloud Print [™] , Canon PRINT Business, and uniFLOW Online. A range of software and MEAP-based solutions are available to provide printing from
Fonts Print Features	mobile devices or internet-connected devices and cloud-based services depending of
	your requirements. Please contact your sales representative for further information.
	PS Fonts: 136 Roman PCL Fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WTJ/K/S/T*1
	(Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts*2
	*1 Optional PCL InternationI Font Set-A1 is required. *2 Optional Barcode Printing Kit-D1 is required.
	Secured Print, Secure Watermark, Header/Footer, Page Layout, Two-sided Printing,
	Mixed Paper Sizes/Orientations, Front/Back Covers, Toner Reduction, Poster Printing, Forced Hold Printing, Print Date, Scheduled Printing, Printing Using a Virtual Printer
Operating System	UFRII: Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/
As of July,2019	Server 2016/Server 2019, MAC OS X (10.10 or later)
	PCL: Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/ Server 2016/Server 2019
	PS: Windows® 7/ 8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/
	Server 2016/Server 2019, MAC OS X (10.10 or later) PPD: Windows® 7/8.1/10, MAC OS X (10.9 or later)
Copy Specifications	
Copy Speed	iR-ADV DX 8705: Up to 105 ppm (A4), Up to 54 ppm (A3), Up to 76 ppm (A4R), Up to 10
	ppm (A5R) iR-ADV DX 8795: Up to 95 ppm (A4), Up to 50 ppm (A3), Up to 69 ppm (A4R), Up to 95
	ppm (A5R)
	iR-ADV DX 8786: Up to 86 ppm (A4), Up to 44 ppm (A3), Up to 63 ppm (A4R), Up to 86 ppm (A5R)
First-Copy-Out Time (A4)	Approx. 2.7 seconds or less
Copy Resolution (dpi)	600 x 600
Aultiple Copies	Up to 9,999 Copies
Copy Density Magnification	Automatic or Manual (9 Levels) Variable Zoom: 25% to 400% (1% Increments)
Magnification	Variable Zoom: 25% to 400% (1% Increments) Preset Reduction/Enlargement: 25%, 50%, 61%, 70%, 81%, 86%, 100% (1:1), 115%, 122%,
	141%, 200%, 400%
Copy Features	Preset R/E Ratios by Area, Two-sided, Density Adjustment, Original Type Selection, Interrupt Mode, Book to Two Pages, Two-sided Original, Job Build, N on 1, Add Cover,
	Insert Sheets, Different Size Originals, Page Numbering, Copy Set Numbering,
	Sharpness, Erase Frame, Secure Watermark, Print Date, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Mirror Image, Store in Mail Box,
	Superimpose Image, Copy ID Card, Skip Blank Pages, Free Size Original, Reserved
	Copy, Copy Sample
Scan Specifications	
Туре	Single Pass Duplexing Automatic Document Feeder (2-sided to 2-sided (Automatic))

Document Feeder Paper Capacity (80 gsm)	Up to 200 Sheets
Acceptable Originals and Weights	Platen: Sheet, Book, and 3-Dimensional Objects Document Feeder Media Weight:
	1-sided Scanning: 38 to 220 gsm (BW), 64 to 220 gsm (CL) 2-sided Scanning: 38 to 220 gsm (BW), 64 to 220 gsm (CL)
	* An acceptable weights of A6R or smaller is 50 to 220 gsm.
Supported Media Size	Platen Max. Scanning Size: Up to 297.0 x 431.8 mm Document Feeder Media Size:
	A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, B6R Custom Size: 70.0 x 139.7 mm to 304.8 x 431.8 mm
Scan Speed (ipm: BW/CL; A4)	1-sided Scanning: 135/135 (300 x 300 dpi, Send), 135/80 (600 x 600 dpi, Copy) 2-sided Scanning: 270/270 (300 x 300 dpi, Send), 165/90 (600 x 600 dpi, Copy)
Scan Resolution (dpi)	Scan for Copy: 600 x 600 Scan for Send: (Push) 600 x 600 (SMB/FTP/WebDAV/IFAX), (Pull) 600 x 600
	Scan for Fax: 600 x 600
Pull Scan Specifications	Colour Network ScanGear2. For both TWAIN and WIA. Supported OS: Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server
Scan Method	2012 R2/Server 2016 Push Scan, Pull Scan, Scan to Box, Scan to Advanced Box, Scan to Network, Scan to
Sond Specifications	USB Memory Key, Scan to Mobile Device, Scan to Cloud (uniFLOW Online)
Send Specifications Destination	Standard: E-mail/Internet FAX (SMTP) SMB3.0 FTP WebDAV Mail Box
Address Book	Optional: Super G3 FAX, IP Fax LDAP (2000)/Local (1600)/Speed Dial (200)
Send Resolution (dpi)	Push: Up to 600 x 600
Communication Protocol	Pull: Up to 600 × 600 File: FTP (TCP/IP), SMB3.0 (TCP/IP), WebDAV
File Format	E-mail/I-Fax: SMTP, POP3 Standard: TIFF, JPEG, PDF (Compact, Searchable, Apply Policy, Optimise for Web,
nic romat	DFI/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML
Universal Cond Fastures	(PowerPoint, Word)
Universal Send Features	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed
	Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Pages
Fax Specifications Maximum Number of	4
Connection Lines	
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution (dpi) Sending/Receiving Size	400 x 400 (Ultra Fine), 200 x 400 (Super Fine), 200 x 200 (Fine), 200 x 100 (Normal) Sending: A3, A4, A4R, A5 ^{e1} , A5R ^{e1} , B4, B5 ^{e2} , B5R ^{e1}
	Receiving: A3, B4, A4, A4R, A5R , B5, B5R *1 Sent as A4
Fax Memory	*2 Sent as B4 short Up to 30,000 Pages (2,000 Jobs)
Speed Dials	Max. 200
Group Dials/Destinations Sequential Broadcast	Max. 199 Dials Max. 256 Addresses
Memory Backup	Yes
Fax Features	Sender's Name (TTI), Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Interrupt Transmission,
	Sequential Broadcasting, Password/Subaddress Sending, Confidential Mailbox, 2 on 1 Log
Store Specifications	
Mail Box (Number Supported)	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes Maximum 30,000 Pages (2,000 Jobs) Stored
Advanced Box	Communication Protocol: SMB or WebDAV Supported Client PC: Windows® 8.1/10
Advanced Dev Available Disc Course	Concurrent Connections (Max.): SMB: 64, WebDAV: 3
Advanced Box Available Disc Space Advanced Box Features	Standard:16 GB (with option: max. 480 GB) Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a
	Password, Search, File Preview, Authentication Management, Open to Public, URI TX, Backup/Restore
Security Specifications	
Authentication and Access Control	Standard: User Authentication (Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Department ID
	Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN
	Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)
Document Security	Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print*), Receive Data Security (Confidential Fax Inbox Forwarding Received
	Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/XPS,
	User Signature PDF/XPS, Adobe LiveCycle® Rights Management ES2.5 Integration), BOX Security (Mail Box Password Protected, Advanced Box Access Control), Send
	Data Security (Setting for requesting password input per transmission, Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver
	Transmissions, Allow/Restrict Sending from History, S/MIME Support), Scan Lock (QR code), Document Tracking (Secure Watermark)
Network Security	*1 Requires uniFLOW Online/uniFLOW TLS 1.3, IPSec, IEEE802.1X Authentication, SNMP V3.0, Firewall Functionality (IP/MAC
	Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), Disabling Unused Functions (Enabling/Disabling Protocols/Applications,
	Enabling/Disabling Remote UI, Enabling/Disabling USB Interface), G3 FAX Separation from LAN, USB Port Separation from LAN, Prohibit the Execution of Files Stored in
	Advanced Box in the MFP, Scan and Send-virus Concerns for E-mail Reception
Device Security	Protecting HDD Data (HDD Data Encryption (FIPS140-2 Validated), HDD Data Overwrite Erase, HDD Lock), Standard HDD Initialise, Trusted Platform Module (TPM), Job Log
	Conceal Function, Protecting MFD Software Integrity, Checking MFD Software Integrity (Verify System at Startup, Runtime Intrusion Detection)
Device Management and Auditing	Administrator Password, Digital Certificate And Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event
Enderson 10 million	Management), Image Data Logging, Security Policy Setting
Environmental Specifications Operating Environment	Temperature: 10 to 30 °C
Power Source	Humidity: 20 to 80 % RH (Relative Humidity) 220–240V, 50/60Hz, 10A
Power Consumption	Maximum: Approx. 2,400 W
	Standby: Approx. 217 W*1 Sleep Mode: Approx. 0.9 W*2
	*1 Reference Value: Measured One Unit *2 0.9 W Sleep mode may not be possible in all circumstances due to certain settings.
Consumables	
	NPG-53 Toner Black
Toner Cartridge/s Toner (Estimated Yield @ 6%	70,000 Pages
Toner Cartridge/s Toner (Estimated Yield @ 6% Coverage)	-
Toner Cartridge/s Toner (Estimated Yield @ 6%	-
Toner Cartridge/s Toner (Estimated Yield @ 6% Coverage) Software and Printer Manager Tracking and Reporting Remote Management Tools	nent Universal Login Manager (ULM), uniFLOW Online Express eMaintenance, Content Delivery System
Toner Cartridge/s Toner (Estimated Yield @ 6% Coverage) Software and Printer Manager Tracking and Reporting	n <mark>ent</mark> Universal Login Manager (ULM), uniFLOW Online Express
Toner Cartridge/s Toner (Estimated Yield @ 6% Coverage) Software and Printer Manager Tracking and Reporting Remote Management Tools Scanning Software Optimisation Tools Platform	Ment Universal Login Manager (ULM), uniFLOW Online Express eMaintenance, Content Delivery System Network ScanGear Canon Driver Configuration Tool, NetSpot Device Installer MEAP (Multifunctional Embedded Application Platform)
Toner Cartridge/s Toner (Estimated Yield @ 6% Coverage) Software and Printer Manager Tracking and Reporting Remote Management Tools Scanning Software Optimisation Tools	Ment Universal Login Manager (ULM), uniFLOW Online Express eMaintenance, Content Delivery System Network ScanGear Canon Driver Configuration Tool, NetSpot Device Installer MEAP (Multifunctional Embedded Application Platform)

			T 0 1 / 1 00
Print Resolution (dpi) Standard Page Description Language(s)	1,200 x 1,200, 600 x 600 PCL6, Adobe PostScript 3	Staple Finisher-W1 PRO	Tray Capacity (with 80 gsm paper): Upper Tray: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R: 1,000 Sheets Z-Fold: A3, B4: 30 Sheets Half-Fold: A4R 50 Sheets
Memory Hard Disk Drive	8 GB (2 × 4 GB) 500 GB SATA		Lower Tray:
Processor	Intel Pentium G4400 (3.3 GHz)		If the High-volume Stack Mode is set to "ON": A4, B5: 4,000 Sheets
System	FS350Pro		A4R, B5R: 2,000 Sheets SRA3, A3, B4: 1500 Sheets
Fonts	PS: 138 Fonts PCL: 113 Fonts		If the High-volume Stack Mode is set to "OFF":
Supported Operating Systems	Windows® 7 64 bit/Windows® 8.1 64 bit/Windows® 10 64 bit/Windows® Server 2008 R2 64 bit Only/Windows® Server 2012 64 bit Only (Only Printer Driver Support)/Windows® Server 2018 R2 64 bit Only/Windows® Server 2016 R2 64 bit Only, MAC OS (1011, 1012,		A4, B5: 2,000 Sheets SRA3, A3, A4R, B4, B5R: 1,000 Sheets Paper Weight: 52 to 256 gsm Staple Position: Comer, Double
Interface	10.13, 10.14) 2 x Ethernet (1000Base-T/100Base-TX/10Base-T), USB 3.0 x 2 (Rear), x 3 (Front on Fiery		Staple Capacity: Corner and Double Stapling: A4, B5: 100 Sheets (52 to 80 gsm)
Network Protocols	Quick Touch™), USB 2.0 x4 (Rear) TCP/IP (FTP, SMTP, POP, HTTP, SNMP, LDAP, SLP, SMB, LPD, IPP, WS-Discovery,		A3, A4R, B4, B5R: 50 sheets (52 to 81.4 gsm) Power Source: 220–240V/50–60 Hz/8A
	Bonjour, Direct Mobile Printing, Port9100, SNTP, 802.1X, DHCP, DNS, NTP)		Dimensions (W x D x H): 890 x 792 x 1,239 mm (when the extension tray is extended)
Direct Print VDP	PDF1.7, EPS, TIFF6, JDF1.4/JMF (Optional) FreeForm v1, v2.1, PPML, PDF/VT-1, PDF/VT-2, Creo VPS		Weight: Approx. 130 kg
Fiery Print Controller Standard	Fiery Command WorkStation6/Paper Catalog/Fiery Remote Scan/Fiery Hot Folders &	Booklet Finisher-W1 PRO	(Includes the above Staple Finisher-W1 PRO basic specifications). Saddle Stitch Paper Size: SRA3, A3, A4R, B4,
Features Fiery Print Controller Options	Virtual Printers/Fiery JDF Fiery Impose/Fiery Compose/Fiery Impose and Compose/Removable HDD Kit/Fiery Image Viewer		Custom Size (210.0 x 279.4 mm to 330.2 x 487.7 mm) Saddle Stitch Staple Capacity: 25 Sheets (52 to 80 gsm) (including 1 cover sheet up to 256 gsm)
HW Platform	NX One		Non Staple Folded Bunch Capacity: Up to 5 Sheets (52 to 209 gsm) Power Source: 220-240V, 50-60 Hz, 8A
Base OS Power Source	Windows® 10 IoT Enterprise 2019 LTSC AC 100–240V, 50Hz/60Hz, 3.0A (100V) – 1.5A (240V)		Dimensions (W x D x H): 1,060 x 792 x 1,239 mm
Maximum Power Consumption	53 W		(when the extension tray is extended) Weight: Approx. 180 kg
Dimensions (W x D x H)	203 x 248 x 384 mm	2/3 Hole Puncher Unit-A1	(Requires either the Staple Finisher-AC1 or Booklet Finisher-AC1).
Weight Paper Supply Options	Server Unit Only: Approx. 5.9 kg		Two or Three Holes Acceptable Punch Paper Weight: 52 to 256 gsm
Paper Deck Unit-E1	Paper Capacity: 3,500 Sheets (80 gsm)		Acceptable Punch Paper Size: Two Holes: A3, A4, A4R, A5, B4, B5, B5R
	Paper Type: Thin, Plain, Recycled, Colour, Heavy, Bond, Pre-punched, Letterhead Paper Size: A4, B5		Three Holes: A3, A4, B4, B5
	Paper Weight: 52 to 256 gsm	2/4 Hole Puncher Unit-A1	Power Source: From the Finisher (Requires either the Staple Finisher-AC1 or Booklet Finisher-AC1).
	Power Source: From the Main Unit Dimensions (W \times D \times H): 340 \times 630 \times 572 mm (attached to the main unit)	2	Two or Four Holes
POD Deck Lite-C1	Weight: Approx. 34 kg Paper Capacity: 3,500 Sheets (80 qsm)		Acceptable Punch Paper Weight: 52 to 256 gsm Acceptable Punch Paper Size:
FOD DECK LITE-CI	Paper Type: Thin, Plain, Recycled, Colour, Heavy, Tracing, Bond, Transparency, Label, Pre-punched, Letterhead, Tab		Two Holes: A3, A4, A4R, A5, B4, B5, B5R Four Holes: A3, A4 Power Source: From the Finisher
	Paper Size: SRA3, A3, A4, A4R, A5R, B4, B5, B5R	4 Hole Puncher Unit-A1	(Requires either the Staple Finisher-AC1 or Booklet Finisher-AC1).
	Custom Size (139.7 x 182.0 mm to 330.2 x 487.7 mm) Paper Weight: 52 to 256 gsm		Four Holes Acceptable Punch Paper Weight: 52 to 256 gsm
	Power Source: 220–240 V, 50/60 Hz, 1.2 A		Acceptable Punch Paper Size: Four Holes: A3, A4, A4R, A5, B4, B5, B5R
	Dimensions (W x D x H): 633 x 686 x 574 mm (attached to the main unit) Weight: Approx. 68 kg		Power Source: From the Finisher
Output Options*	*Paper capacity may vary with different of paper type/size.	Puncher Unit-BF1	(Requires either the Staple Finisher-X1 or Booklet Finisher-X1). Two or Three Holes
Copy Tray-R2	Provides a simple tray for basic output needs. Capacity: 250/100 Sheets (1-sided/2-sided, 80 gsm)		Acceptable Punch Paper Weight: 52 to 256 gsm
	Dimensions (W x D x H): 420 x 382 x 175 mm		Acceptable Punch Paper Size: Two Holes: A3, A4, A4R, A5
Staple Finisher-AC1* * Only available for iR-ADV DX 8786i	Tray Capacity (with 80 gsm paper): Upper Tray: A4, A5, A5R, A6R, B5: 250 Sheets		Three Holes: A3, A4 Power Source: From the Finisher
	A3, A4R, B4, B5R: 125 Sheets	Puncher Unit-BG1	(Requires either the Staple Finisher-X1 or Booklet Finisher-X1).
	SRA3: 30 Sheets Mid Tray: Same as Upper Tray		Two or Four Holes Acceptable Punch Paper Weight: 52 to 256 gsm
	Lower Tray: A4, A5, A5R, B5: 3,000 Sheets SRA3, A3, A4R, B4, B5R: 1,500 Sheets		Acceptable Punch Paper Size:
	A6R: 250 Sheets		Two Holes: A3, A4, A4R, A5, B5R Four Holes: A3, A4
	Paper Weight: 52 to 256 gsm Staple Position: Corner, Double	Dura da su Linita Di M	Power Source: From the Finisher
	Staple Capacity: A4, B5: 65 Sheets (52 to 90 gsm)	Puncher Unit-BH1	(Requires either the Staple Finisher-X1 or Booklet Finisher-X1). Four Holes
	A3, A4R, B4: 40 Sheets (52 to 90 gsm)		Acceptable Punch Paper Weight: 52 to 256 gsm Acceptable Punch Paper Size:
	Eco Staple: A3, A4 5 Sheets (52 to 64 gsm)		Four Holes: A3, A4, A4R, A5, B4, B5, B5R Power Source: From the Finisher
	4 Sheets (65 to 81.4 gsm) 3 Sheets (81.5 to 105 gsm)	Puncher Unit-BS1	(Requires either the Staple Finisher-W1 PRO or Booklet Finisher-W1 PRO).
	Staple On-demand: 65 Sheets (52 to 90 gsm)		Two or Three Holes Acceptable Punch Paper Weight: 52 to 256 gsm
	Power Source: From the Main Unit Dimensions (W \times D \times H): 656 \times 623 \times 1,195 mm		Acceptable Punch Paper Size:
	(when the extension tray and rotary tray are extended) Weight: Approx. 36 kg		Two Holes: Custom Size (182.0 x 182.0 mm to 297.0 x 432.0 mm) Threee Holes: A3, A4, Custom Size (240.0 x 182.0 mm to 297.0 x 432.0 mm)
Booklet Finisher-AC1*	(Includes the above Staple Finisher-AC1 basic staple specifications).		Power Supply: From the Finisher
* Only available for iR-ADV DX 8786i	Saddle Stitch Paper Size: A3, A4R, B4, Custom Size (182.0 x 210.0 mm to 304.8 x 457.2 mm)	Puncher Unit-BT1	(Requires either the Staple Finisher-W1 PRO or Booklet Finisher-W1 PRO). Two or Four Holes
	Saddle Stitch Staple Capacity: 20 Sheets x 10 Sets (52 to 81.4 gsm)		Acceptable Punch Paper Weight: 52 to 256 gsm Acceptable Punch Paper Size:
	(including 1 cover sheet up to 256 gsm) Non Staple Folded Bunch Capacity: 3 Sheets (52 to 105 gsm)		Two Holes A3, A4, A4R, A5, B4, B5, B5R, Custom Size (182.0 x 182.0 mm to
	Power Source: From the Main Unit Dimensions (W \times D \times H): 656 \times 623 \times 1,195 mm		297.0 x 432.0 mm, excluding 203 x 257 mm to 297 x 270 mm) Four holes A3, A4, B4, B5, Custom Size (257.0 x 182.0 mm to
	(when the extension tray and rotary tray are extended)		297.0 x 432.0 mm) Power Supply: From the Finisher
Staple Finisher-X1	Weight: Approx. 60 kg Tray Capacity (with 80 gsm paper):	Puncher Unit-BU1	(Requires either the Staple Finisher-W1 PRO or Booklet Finisher-W1 PRO).
	Upper Tray: A4, A5R, B5: 1,500 Sheets SRA3, A3, A4R, A5, B4, B5R: 750 Sheets		Four Holes Acceptable Punch Paper Weight: 52 to 256 gsm
	A6R: 250 Sheets		Acceptable Punch Paper Size:
	Mid Tray: A4, A5R, B5: 250 Sheets A3, A4R, A5, A6R, B4, B5R: 125 Sheets		Four holes A3, A4, A4R, A5, B4, B5, Custom Size (257.0 x 182.0 mm to 297.0 x 432.0 mm)
2 2 1 1	SRA3: 30 Sheets	Multi Function Professional	Power Supply: From the Finisher (Requires either the Staple Finisher-X1, Booklet Finisher-X1, Staple Finisher-W1 PRO or
	Lower Tray: A4, B5: 2,500 Sheets (Cascade-load Mode) A4, A5R, B5: 1,500 Sheets	Multi Function Professional Puncher-B1	Booklet Finisher-W1 PRO).
	SRA3, A3, A4R, A5, B4, B5R: 750 Sheets A6R: 250 Sheets		Acceptable Punch Paper Weight: Bypass: 75 to 256 gsm
	Paper Weight: 52 to 256 gsm		Punch: 75 to 256 gsm
	Staple Position: Corner, Double Staple Capacity:		Acceptable Punch Paper Size: Bypass: 100 x 148 mm to 330.2 x 487.7 mm
	A4, B5: 100 Sheets (52 to 80 gsm) A3, A4R, B4: 50 Sheets (52 to 80 gsm)		Punch: A3, A4, A4R, A5 Supported Punch Dies (Optional):
	Power Source: 100–240V AC, 50–60Hz, 2.8A Dimensions (W x D x H): 782 x 765 x 1,040 mm		Loose Leaf (2- or 4- hole), Velo Bind (12-hole), Plastic Comb (21-hole), Twin Loop (23- or 34- hole), Colour Coil (47-hole)
	(when the extension tray is extended)		Power Source: 230V, 50Hz, 2.0 A
Booklet Finisher-X1	Weight: Approx. 64 kg (Includes the above Staple Finisher-X1 basic specifications).		Dimensions (W x D x H): 445 x 795 x 1,040 mm Weight: 102 kg
SSSREET HISHEFAT	Saddle Stitch Paper Size: SRA3, A3, A4R, B4,	Inner Booklet Trimmer-A1	(Requires Booklet Finisher-X1).
	Custom Size (195.0 x 270.0 mm to 330.2 x 457.2 mm) Saddle Stitch Staple Capacity: 20 Sheets x 5 Sets (60 to 81.4 gsm)		Waste Tray Capacity: Approx. 1,500 Sheets Acceptable Paper Weight: 60 to 256 gsm
	(including 1 cover sheet up to 256 gsm) Non Staple Folded Bunch Capacity: 5 Sheets (60 to 105 gsm)		Trim Amount: 2 to 20 mm Acceptable Paper Size: SRA3, A3, A4R, B4,
	Power Source: 100–240V AC, 50–60 Hz, 2.8A		Custom Size: 195 x 270 mm to 330.2 x 457.2 mm
	Dimensions (W x D x H): 896 x 765 x 1,040 mm (when the extension tray is extended)	Booklet Trimmer-F1	Power Source: from the Finisher (Requires Booklet Finisher-W1 PRO).
	Weight: Approx. 110 kg	Sookiet minitel 1	Booklet Capacity: 10 Booklets (Booklet Size: A4, 50 Sheets, 80 gsm)
			Acceptable Paper Weight: 52 to 256 gsm, 64 to 300 gsm (cover sheet only Acceptable Paper Size: SRA3, A3, A4R, B4
			Custom Size: 210.0 x 279.4 mm to 330.2 x 487.7 mm) Trim Amount: 2 to 28 mm
			Trimming Capacity: Up to 25 Sheets (50 Sheets by Half-fold) (52 to 80 gsm)
			Waste Tray Capacity: Approx. 5,000 Sheets
			Power Source: From the Booklet Finisher-W1 PRO
			Power Source: From the Booklet Finisher-WI PRO Dimensions: 2,095 x 790 x 1,040 mm (Including Joint) Weight: Approx. 178 kg

Document Insertion Unit-N1	(Requires the Staple Finisher-X1, Booklet Finisher-X1, Staple Finisher-W1 PRO or		
	Booklet Finisher-W1 PRO).		
	Number of Trays: 2 Tray Capacity (with 80gsm paper):		
	Upper tray: 200 Sheets		
	Lower tray: 200 Sheets		
	Acceptable Paper Type: Thin, Plain, Recycled, Colour, Heavy, Coated, Tracing, Bond,		
	Pre-punched, Letterhead, Tab		
	Acceptable Paper Size: SRA3, A3, A4, A4R, B4, B5, B5R Custom Size: 182 x 182 mm to 330.2 x 487.7 mm		
	Acceptable Paper Weight: 52 to 256 gsm		
	Power Supply: 100–240V, 50/60Hz, 1.0 A		
	Dimensions (W x D x H): 336 x 793 x 1,407 mm		
	(attached to the device: width excluding document tray)		
	Weight: Approx. 61 kg		
Paper Folding Unit-J1	(Requires the Staple Finisher-X1, Booklet Finisher-X1, Staple Finisher-W1 PRO or Booklet Finisher-W1 PRO).		
	Supported Folding Type: Z-Fold, C-Fold, Accordion-Z-Fold, Double Parallel-Fold, Half-Fold		
	Acceptable Paper Type: Thin, Plain, Recycled, Colour, Bond		
	Acceptable Paper Size:		
	Z-Fold: A3, A4R, B4 C-Fold, Accordion Z-Fold, Half-Fold, Double-parallel Fold: A4R		
	C-Fold, Accordion 2-Fold, Half-Fold, Double-parallel Fold: A4R Acceptable Paper Weight:		
	Z-Fold, Accordion Z-Fold, C-Fold, Half-Fold: 52 to 105gsm		
	Double Parallel Fold: 52 to 90 gsm		
	Output Capacity (with 80 gsm paper):		
	C-Fold/Accordion Z-Fold: Approx. 40 Sheets		
	Double Parallel-Fold: Approx. 25 Sheets with Staple Finisher-X1 or Saddle Finisher-X1 (in total)		
	Z-Fold: A3. B4: 70 Sheets. A4R: 30 Sheets		
	Half-fold: A4R: 30 Sheets		
	with Staple Finisher-W1 PRO or Saddle Finisher-W1 PRO (in total)		
	Z-Fold: A3, B4: 60 Sheets		
	Half-Fold: A4R: 50 Sheets Power Source: From the Finisher		
	Dimensions (W x D x H): 336 x 793 x 1,190 mm		
	Weight: Approx. 71 kg		
Hardware Accessories			
Card Readers	Copy Card Reader-F1, Copy Card Reader Attachment-A4		
Others	Upright Control Panel-J1, Utility Tray-B1, Tab Feeding Attachment Kit-B1, Numeric Keypad-A1, Finisher Jogger Kit-A1, Printer Cover-H2		
Security Options			
Data Security	2.5 inch/250 GB HDD-N1, 2.5 inch/1 TB HDD-P1, HDD Mirroring Kit-J1		
system and Controller Option	S		
rint Accessories	PCL International Font Set-A1, PCL Printer Kit-BD1, PS Printer Kit-BD1		
Barcode Printing	Barcode Printing Kit-D1		
FI-Fiery Based Controller	imagePASS-Y3 V1.1		
FI-Fiery Based Controller Options	Fiery Impose, Fiery Compose, Fiery Impose and Compose, Fiery imageViewer, Removable HDD Kit-B6		
System Accessories	Copy Control Interface Kit-A1, Serial Interface Kit-K3, Connection Kit-A2 for Bluetooth		
,	LE, NFC Kit-E1		
ax Accessories	LE, NFC Kit-E1 Super G3 FAX Board-AS1, Super G3 2nd Line Fax Board-AS1, Super G3 3rd/4th Line		
ax Accessories Dther Options Accessibility Accessories	LE, NFC Kit-E1 Super G3 FAX Board-AS1, Super G3 2nd Line Fax Board-AS1, Super G3 3rd/4th Line		









Canon Australia Pty Ltd 1800 444 199 canon.com.au/business Canon New Zealand Ltd 0800 222 666 canon.co.nz/business